



Be informed quickly in the event of a fire Combinations of EI ELECTRONICS and MOBEYE alarm forwarding

To provide effective fire and carbon monoxide detection, complete with siren and alarm reporting, Mobeye communication modules integrate coherently with Ei Electronics detectors. Multiple battery-powered detectors (for smoke, heat, and carbon monoxide) can be wirelessly interconnected. All Ei Electronics components have a battery that lasts 10 years. Using the Ei Electronics relay module and with minimal installation effort they are integrated with Mobeye communication technology, ready to send alarm notifications to preset alarm contacts. The alarm message can go to your own numbers via push message, call, SMS and email and/or to an emergency room.

Select and customize your configuration from the following components.

Product	Function	Number	Remark
Ei650RF	Optical smoke detector	Max. 20	
Ei650iRF	Optical smoke detector		Incl. automatic dust compensation
Ei630iRF	Heat detector		Incl. automatic dust compensation
Ei660iRF	Smoke + heat detector		
Ei208WRF	CO-detector		
Ei407RF	Manual call point		To activate sirens and alarms
Ei450RF	Control unit		To test, locate and silence the detectors
Relay module	Ei428RF	1 (required)	Needs 230V mains power (1 socket) (Mobeye Kit: including wiring, power cord, quick guide)
Mobeye CM4100	Alarm communicator	1 (required)	
SIM/Portal	SIM connection, maintenance in portal, alarm forwarding	1 (required)	

Reliable fire/CO detectors,
with siren and alarm reporting

online management tool
and communication checks

alarm via push-app, call,
SMS, email and/or control room

Do you need more information or help? We are happy to advise you.